

# Theoretical Computer Science - Bridging Course

## Summer Term 2018

### Exercise Sheet 4

for getting feedback submit electronically by 06:00 am, Monday, May 28th, 2018

#### Exercise 1: Context-Free Grammar (3+2 Points)

For each of the following languages, give a context-free grammar to accept the language.

(a)  $L_1 = \{w\#w' \mid w^R \text{ is a substring of } w', \text{ and } w, w' \in \{0, 1\}^*\}$ .<sup>1</sup>

(b)  $L_2 = \{0^i 1^j 2^k \mid i \neq j \text{ or } j \neq k\}$

#### Exercise 2: Chomsky Normal Form (5 Points)

Consider the following context-free grammar (CFG):

$$\begin{aligned} S &\rightarrow aSb \mid D \\ D &\rightarrow ccDcc \mid \varepsilon \end{aligned}$$

Convert this CFG into an equivalent one in Chomsky Normal Form. Give the grammar you obtained after each step of the conversion algorithm.

#### Exercise 3: Constructing Pushdown Automata (4 Points)

Consider the language  $L = \{a^n b^{2m} b a^n \mid m, n > 0\}$  over the alphabet  $\Sigma = \{a, b\}$ . Construct a PDA  $\mathcal{A}$  with  $L(\mathcal{A}) = L$ .

#### Exercise 4: Pumping Lemma for Context-Free Languages (3+3 Points)

Use the pumping lemma to show that the following languages over the alphabet  $\Sigma = \{a, b\}$  are not context free:

(a)  $\{ww \mid w \in \{a, b\}^*\}$

(b)  $\{a^n b a^{2n} b a^{3n} \mid n \geq 0\}$

---

<sup>1</sup> $w^R$  is achieved by reversing the order of the symbols in  $w$ .