



# Algorithms and Datastructures

## Winter Term 2024

### Exercise Sheet 3

Due: Wednesday, May 8th, 12pm

#### Exercise 1: Bucket Sort

(7 Points)

*Bucketsort* is an algorithm to stably sort an array  $A[0..n-1]$  of  $n$  elements where the sorting keys of the elements take values in  $\{0, \dots, k\}$ . That is, we have a function `key` assigning a key  $\text{key}(x) \in \{0, \dots, k\}$  to each  $x \in A$ .

The algorithm works as follows. First we construct an array  $B[0..k]$  consisting of (initially empty) FIFO queues. That is, for each  $i \in \{0, \dots, k\}$ ,  $B[i]$  is a FIFO queue. Then we iterate through  $A$  and for each  $j \in \{0, \dots, n-1\}$  we attach  $A[j]$  to the queue  $B[\text{key}(A[j])]$  using the function `enqueue`.

Finally we empty all queues  $B[0], \dots, B[k]$  using `dequeue` and write the returned values back to  $A$ , one after the other. After that,  $A$  is sorted with respect to `key` and elements  $x, y \in A$  with  $\text{key}(x) = \text{key}(y)$  are in the same order as before.

Implement *Bucketsort* based on this description<sup>1</sup>. You can use the template `BucketSort.py` which uses an implementation of FIFO queues that are available in `Queue.py` und `ListElement.py`.<sup>2</sup>

#### Exercise 2: Radix Sort

(13 Points)

Assume we want to sort an array  $A[0..n-1]$  of size  $n$  containing integer values from  $\{0, \dots, k\}$  for some  $k \in \mathbb{N}$ . We describe the algorithm *Radixsort* which uses *Bucketsort* as a subroutine.

Let  $m = \lfloor \log_b k \rfloor$ . We assume each key  $x \in A$  is given in base- $b$  representation, i.e.,  $x = \sum_{i=0}^m c_i \cdot b^i$  for some  $c_i \in \{0, \dots, b-1\}$ . First we sort the keys according to  $c_0$  using *Bucketsort*, afterwards we sort according to  $c_1$  and so on.<sup>3</sup>

- Implement *Radixsort* based on this description. You may assume  $b = 10$ , i.e., your algorithm should work for arrays containing numbers in base-10 representation. Use *Bucketsort* as a subroutine. If you did not solve task 1, you may use a library function (e.g., `sorted`) as alternative to *Bucketsort*. (7 Points)
- Compare the runtimes of *Bucketsort* and *Radixsort*. For both algorithms and each  $k \in \{2 \cdot i \cdot 10^4 \mid i = 1, \dots, 60\}$ , use an array of fixed size  $n = 10^4$  with randomly chosen keys from  $\{0, \dots, k\}$  as input and plot the runtimes. Shortly discuss your results in `experiences.txt`. (3 Points)
- Explain the asymptotic runtime of your implementations of *Bucketsort* und *Radixsort* depending on  $n$  and  $k$ . (3 Points)

<sup>1</sup>Remember to make unit-tests and to add comments to your source code.

<sup>2</sup>You are allowed to use `librarays`, but note that the names of the methods may differ.

<sup>3</sup>The  $i$ -th digit  $c_i$  of a number  $x \in \mathbb{N}$  in base- $b$  representation (i.e.,  $x = c_0 \cdot b^0 + c_1 \cdot b^1 + c_2 \cdot b^2 + \dots$ ), can be obtained via the formula  $c_i = (x \bmod b^{i+1}) \operatorname{div} b^i$ , where `mod` is the modulo operation and `div` the integer division.